



Equipment Specifications

Clearances

Left side	12"/30cm
Right side	12"/30cm
Overhead	14"/35cm
Floor	36"/91cm
Front	36"/91cm

Plumbing

3/4"/2cm Hose Bib with 5gpm/.14Lpm @
30psi/20.6bars. 120°F/49°C

Electrical

208-230V, 9A GFCI

Installation Specifications

Electrical:

208V - 230V 15A hardwired through service disconnect at pump. CAUTION: In all installations the use of a Ground Fault Interrupter (GFI) in the power supply circuit is essential for personal safety.

Water:

One (1) warm water outlet 120°F/49°C. MAX with standard 3/4"/1.9cm hose bib with shut-off valve. A pressure gauge in the water line can be helpful although it is not mandatory. A minimum of 5 gal. / 19L per minute and a line pressure not less than 30psi/20.6bars, is required.

Location:

Heated utility room or closet with ventilation. Minimum 14in/.35m clearance above unit required to remove cover. The cover must be removed for servicing the unit. The unit can be serviced without removing it from the wall.

General Recommendations:

Floor drains are essential in new facilities to receive the greatest utilization and maximum efficiency of your SPRAY MASTER Pressure Washer. Floor materials and wall coverings which can be cleaned with pressurized water are desirable. Locate electrical outlets above washing areas.